


- General purpose DC Miniature Circuit
  Breakers
- Tested according to IEC / EN 60947-2
- Rated operating voltage U 220 V DC per pole
- Rated current 1 up to 63 A
- Rated short circuit breaking capacity I<sub>cu</sub> 10 kA
- 1 and 2 pole versions
- Tripping characteristics C, K
- Wide range of accessories

General purpose DC Miniature Circuit Breakers Ex9BD are designed for general direct current aplications. Due to their polarity dependece it is necessary to respect the polarity of the current.


For applications with varying polarity, as e.g. Photovoltaic, please use PV MCB line Ex9BP (see Catalogue of Photovoltaic Components).



Туре Кеу

### NOGLK

#### Accessories



Auxiliary contacts AX3111, AX3122	see page 72
Alarm contact AL3111	see page 72
Auxiliary and alarm contact AXL31	see page 72
Shunt trip releases SHT31, SHT3111	see page 72
Undervoltage releases UVT31, UVT3101, UVT3110	see page 73

All accessories are mounted to the MCBs Ex9BD from the left side and are identical for devices of the line Ex9B and Ex9PN.

### Νοαικ

#### C-Characteristic, 1-pole, 220 V DC

.

Rated current	Width	Char.	Article No.	Туре	Packing
1 A	1 MU	С	103553	Ex9BD 1P C 1A	1/12/144
2 A	1 MU	С	103554	Ex9BD 1P C 2A	1/12/144
3 A	1 MU	С	103555	Ex9BD 1P C 3A	1/12/144
4 A	1 MU	С	103556	Ex9BD 1P C 4A	1/12/144
6 A	1 MU	С	103557	Ex9BD 1P C 6A	1/12/144
10 A	1 MU	С	103558	Ex9BD 1P C 10A	1/12/144
16 A	1 MU	С	103559	Ex9BD 1P C 16A	1/12/144
20 A	1 MU	С	103560	Ex9BD 1P C 20A	1/12/144
25 A	1 MU	С	103561	Ex9BD 1P C 25A	1/12/144
32 A	1 MU	С	103562	Ex9BD 1P C 32A	1/12/144
40 A	1 MU	С	103563	Ex9BD 1P C 40A	1/12/144
50 A	1 MU	С	103564	Ex9BD 1P C 50A	1/12/144
63 A	1 MU	С	103565	Ex9BD 1P C 63A	1/12/144

#### C-Characteristic, 2-pole, 440 V DC

	Rated current
	1 A 2 A
Auguster	3 A
1	4 A
0 0	6 A
15	10 A
	16 A
	20 A
	25 A

Rated current	Width	Char.	Article No.	Туре	Packing
1 A	2 MU	С	103566	Ex9BD 2P C 1A	1/6/72
2 A	2 MU	С	103567	Ex9BD 2P C 2A	1/6/72
3 A	2 MU	С	103568	Ex9BD 2P C 3A	1/6/72
4 A	2 MU	С	103569	Ex9BD 2P C 4A	1/6/72
6 A	2 MU	С	103570	Ex9BD 2P C 6A	1/6/72
10 A	2 MU	С	103571	Ex9BD 2P C 10A	1/6/72
16 A	2 MU	С	103572	Ex9BD 2P C 16A	1/6/72
20 A	2 MU	С	103573	Ex9BD 2P C 20A	1/6/72
25 A	2 MU	С	103574	Ex9BD 2P C 25A	1/6/72
32 A	2 MU	С	103575	Ex9BD 2P C 32A	1/6/72
40 A	2 MU	С	103576	Ex9BD 2P C 40A	1/6/72
50 A	2 MU	С	103577	Ex9BD 2P C 50A	1/6/72
63 A	2 MU	С	103578	Ex9BD 2P C 63A	1/6/72



### K-Characteristic, 1-pole, 220 V DC

.

Rated current	Width	Char.	Article No.	Туре	Packing
1 A	1 MU	К	103605	Ex9BD 1P K 1A	1/12/144
2 A	1 MU	K	103606	Ex9BD 1P K 2A	1/12/144
3 A	1 MU	K	103607	Ex9BD 1P K 3A	1/12/144
4 A	1 MU	K	103608	Ex9BD 1P K 4A	1/12/144
6 A	1 MU	K	103609	Ex9BD 1P K 6A	1/12/144
10 A	1 MU	K	103610	Ex9BD 1P K 10A	1/12/144
16 A	1 MU	K	103611	Ex9BD 1P K 16A	1/12/144
20 A	1 MU	K	103612	Ex9BD 1P K 20A	1/12/144
25 A	1 MU	K	103613	Ex9BD 1P K 25A	1/12/144
32 A	1 MU	K	103614	Ex9BD 1P K 32A	1/12/144
40 A	1 MU	K	103615	Ex9BD 1P K 40A	1/12/144
50 A	1 MU	K	103616	Ex9BD 1P K 50A	1/12/144
63 A	1 MU	K	103617	Ex9BD 1P K 63A	1/12/144

#### K-Characteristic, 2-pole, 440 V DC

	Rated current	Width	Char.	Article No.	Туре	Packing
	1 A	2 MU	К	103618	Ex9BD 2P K 1A	1/6/72
-	2 A	2 MU	К	103619	Ex9BD 2P K 2A	1/6/72
-	3 A	2 MU	K	103620	Ex9BD 2P K 3A	1/6/72
п	4 A	2 MU	К	103621	Ex9BD 2P K 4A	1/6/72
0	6 A	2 MU	K	103622	Ex9BD 2P K 6A	1/6/72
+	10 A	2 MU	K	103623	Ex9BD 2P K 10A	1/6/72
	16 A	2 MU	K	103624	Ex9BD 2P K 16A	1/6/72
	20 A	2 MU	K	103625	Ex9BD 2P K 20A	1/6/72
	25 A	2 MU	K	103626	Ex9BD 2P K 25A	1/6/72
	32 A	2 MU	K	103627	Ex9BD 2P K 32A	1/6/72
	40 A	2 MU	K	103628	Ex9BD 2P K 40A	1/6/72
	50 A	2 MU	K	103629	Ex9BD 2P K 50A	1/6/72
	63 A	2 MU	K	103630	Ex9BD 2P K 63A	1/6/72

Technical data p. 114

